


OVERVIEW





1. Power button	10. HDMI
2. Optical drive *	11. VGA
3. Card reader *	12. Ethernet (RJ-45)
4. Microphone (3.5mm)	13. 4x USB 2.0
5. Headphone / microphone combo jack (3.5mm)	14. Optional ports on expansion cards *
6. 2x USB 3.2 Gen 1	15. Power connector
7. 2x USB 3.2 Gen 2	16. Serial *
8. Audio line-out (3.5mm)	17. Padlock loop *
9. Smart cable clip slots *	18. Kensington Security Slot *

Notes:

- Ports with * are only available on selected models
- More ports are available through the optional expansion cards (not shown on the sample product above)



PERFORMANCE

Processor

Processor Family

AMD Ryzen™ 3 / 5 / 7 Processor

Processor

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Memory Support	Processor Graphics
AMD Ryzen 3 4300G	4	8	3.8GHz	4.0GHz	2MB L2 / 4MB L3	DDR4-3200	AMD Radeon™ Graphics
AMD Ryzen 3 5300G	4	8	4.0GHz	4.2GHz	2MB L2 / 8MB L3	DDR4-3200	AMD Radeon Graphics
AMD Ryzen 5 4600G	6	12	3.7GHz	4.2GHz	3MB L2 / 8MB L3	DDR4-3200	AMD Radeon Graphics
AMD Ryzen 5 5600G	6	12	3.9GHz	4.4GHz	3MB L2 / 16MB L3	DDR4-3200	AMD Radeon Graphics
AMD Ryzen 7 4700G	8	16	3.6GHz	4.4GHz	4MB L2 / 8MB L3	DDR4-3200	AMD Radeon Graphics
AMD Ryzen 7 5700G	8	16	3.8GHz	4.6GHz	4MB L2 / 16MB L3	DDR4-3200	AMD Radeon Graphics

Operating System

Operating System

- Windows® 10 Pro 64
- Windows 10 Home 64
- Windows 11 Pro 64
- Windows 11 Home 64
- Windows 11 DG Windows 10 Pro 64
- No operating system

Graphics

Graphics[1]

Graphics	Туре	Memory	Connector	Max Resolution	Key Features
AMD Radeon Graphics	Integrated	Shared	1x HDMI® 1.4b, 1x VGA	3840x2160@30Hz(HDMI), 2048x1536@50Hz(VGA)	DirectX® 12
AMD Radeon RX 550X	Discrete	4GB GDDR5	1x HDMI 2.0, 1x DP 1.4, 1x VGA	4096x2160@60Hz(HDMI), 3840x2160@60Hz(DP), 2048x1536@85Hz(VGA)	DirectX 12

Notes:

Monitor Support

Monitor Support

Supports up to 2 independent displays via onboard ports (VGA and HDMI), more displays support via discrete graphics

Chipset

Chipset

AMD PRO 565 chipset

Memory^[1]

Max Memory^[2]

Up to 64GB DDR4-3200

Memory Slots

^{1.} The information of integrated graphics are not applicable for the models without integrated graphics (for the details, please refer to processor section)



Two DDR4 UDIMM slots, dual-channel capable

Memory Type

DDR4-3200

Memory Protection

Non-ECC

Notes:

- 1. Recommend to choose the models with more than 4GB for better performance and experience
- 2. The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.

Storage

Storage Support

Up to two drives, 1x 3.5" HDD + 1x M.2 SSD

- 3.5" HDD up to 2TB
- M.2 SSD up to 1TB

Storage Type

Disk Type	Interface	RPM	Security
3.5" SATA HDD	SATA 6Gb/s	7.2K	-
M.2 2242 SSD	PCIe NVMe, PCIe 3.0 x4	-	-
M.2 2280 SSD	PCIe NVMe, PCIe 3.0 x4	-	Opal

RAID

No support

Removable Storage

Optical

- DVD burner (DVD±RW), SATA 1.5Gb/s, slim (9.0mm)
- None

Card Reader

- 3-in-1 card reader (SD, SDHC, SDXC)
- No card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC222 codec

Speakers

- Single speaker, 2W x1
- No speakers

Power Supply

Power Supply

Power	Туре	Efficiency
180W	Fixed	85%
260W	Fixed	85%

DESIGN

Input Device

Keyboard

- Lenovo Calliope Keyboard (USB connector), black
- Lenovo Traditional Keyboard (USB connector), black
- · No keyboard

Mouse



- · Lenovo Calliope Mouse (USB connector), black
- Lenovo Fingerprint Mouse (USB connector), black
- · No mouse

Mechanical

Form Factor

Tower (13.6L)

Dimensions (WxDxH)

Models	Dimensions
All models	145 x 272.3 x 340 mm (5.71 x 10.72 x 13.39 inches)

Weight

Models	Weight
All models	4.7 kg (10.36 lbs)

Case Color

Black (chassis), Grey (bezel)

Bays

- 1x 3.5" disk bay
- · 1x slim ODD bay

Expansion Slots

- One PCle 3.0 x16
- One PCle 3.0 x1
- Two M.2 slots (one for WLAN, one for SSD)

Mounting

None

CONNECTIVITY

Network

Onboard Ethernet

Gigabit Ethernet, Realtek RTL8111HN, 1x RJ45, supports Wake-on-LAN

Optional Ethernet

No optional Ethernet

WLAN + Bluetooth®

- Realtek RTL8852AE, Wi-Fi* 6, 802.11ax Dual Band 2x2 Wi-Fi + Bluetooth 5.0, M.2 card
- Realtek RTL8822CE, 802.11ac Dual Band 2x2 Wi-Fi + Bluetooth 5.0, M.2 card
- Qualcomm® QCA6174A, 802.11ac Dual Band 2x2 Wi-Fi + Bluetooth 5.0, M.2 card
- No WLAN and Bluetooth

Ports^[1]

Front Ports

- 2x USB 3.2 Gen 1
- 2x USB 3.2 Gen 2
- 1x headphone / microphone combo jack (3.5mm)
- 1x microphone (3.5mm)

Optional Front Ports

1x card reader

Rear Ports[2]

- 4x USB 2.0
- 1x VGA
- 1x HDMI-out
- 1x Ethernet (RJ-45)
- 1x line-out (3.5mm)

Optional Rear Ports



1x serial

Notes:

1. The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed. USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

Thunderbolt™ 3: 40 Gbit/s; FireWire 400: 400 Mbit/s; FireWire 800: 800 Mbit/s

2. For video ports on discrete graphics, please see graphics section

Monitor Cable

Monitor Cable

- · HDMI to DVI dongle
- · No monitor cable

SECURITY & PRIVACY

Security

Security Chip

Firmware TPM 2.0 integrated in chipset

Physical Locks

- (Optional) Kensington® Security Slot
- (Optional) Smart Cable Clip
- (Optional) Padlock Loop

Chassis Intrusion Switch

- · Chassis intrusion switch
- No chassis intrusion switch

Fingerprint Reader

- · Touch style fingerprint reader on mouse
- · No fingerprint reader

BIOS Security

- · Administrator password
- Power-on password
- Hard disk password
- Smart USB protection (allows keyboard / mouse only, blocks all storage devices)
- · Individual USB port disablement

MANAGEABILITY

System Management

System Management

None

SERVICE

Warranty

Base Warranty

- 1-year depot service
- 1-year limited onsite service

ENVIRONMENTAL



Operating Environment

Temperature

Operating: 5°C (41°F) to 35°C (95°F)
Storage: -40°C (-40°F) to 60°C (140°F)

Humidity

Operating: 20% to 80%Storage: 10% to 90%

Altitude

Operating: -15.2 m (-50 ft) to 3048 m (10,000 ft)
Storage: -15.2 m (-50 ft) to 12192 m (40,000 ft)

ACCESSORIES

Bundled Accessories

Bundled Accessories

None

CERTIFICATIONS

Green Certifications

Green Certifications

- (Optional) EPEAT™ Silver
- (Optional) ENERGY STAR® 8.0
- TCO
- RoHS / WEEE / REACH









AMD

AMD∄



AMD





мод