OVERVIEW



1. Kensington Security Slot	8. DP out
2. Power Connector	9. Ethernet (RJ-45)
3. HDMI 2.0	10. USB 3.2 Gen 1
4. HDMI 2.0	11. USB 3.2 Gen 1
5. DP 1.2	12. Audio-out (3.5mm)
6. 1x USB-C 3.2 Gen 1 (DP 1.2 Alt Mode))	13. USB-C 3.2 Gen 1
7. USB-B 3.2 Gen 1	14. USB 3.2 Gen 1

PERFORMANCE

Panel

Panel

3-side NearEdgeless, In-Plane Switching

Backlight

WLED

Display Size

34.14 inches

Max View Area

WxH: 799.8 x 334.8 mm

Resolution

3440 x 1440

5440 × 1440

Aspect Ratio

21:9

Pixel Pitch

0.2325 x 0.2325 mm

Dot / Pixel Per Inch

109 dpi

Drightn

Brightness

300 nits

Contrast Ratio

- Contrast Ratio: 1000:1
- Dynamic Contrast Ratio: 3M:1

View Angle (H / V)

Horizontal: 178°, Vertical: 178°

Response Time

- Extreme Mode: 4 ms
- Normal Mode: 6 ms

Refresh Rate

60Hz

Color Gamut

99% sRGB

Color Support

1.07 Billion

Color Depth

10-bit (8-bit+FRC)

Screen Surface Treatment

Anti-glare

Curvature

3800R

Operating System

Operating System

- Windows[®] 10 Support
- Windows 11 Support

Multi-Media

Camera

- ThinkVision® MC 50 monitor webcam (Some models only)
- No bundled webcam (Support ThinkVision MC 50 Monitor Webcam, sold separately)

Microphone

Lenovo

Lenovo

- Built-in dual microphone in MC 50 (Models with MC 50 only)
- No microphone

Speakers

Integrated Speakers, 2x 3W

Power Supply

Power Consumption

- Typical / Max: 36W / 230W
- Switch-off Mode: <0.3W
- Sleep / Off mode: <0.5W
- Internal Power Supply
- Energy Star TEC: 93kWh
- Energy Star Power On: 30W

Voltage Required

AC 100 to 240 V (50-60Hz)

Special Features

Special Features

- Factory Calibration: Avg. Delta E<2
- Picture In Picture (PIP) / Picture By Picture (PBP) Support
- HDR Compliance
- DaisyChain Support (DP out)
- KVM Switch
- Lenovo® ThinkColour (Lenovo Display Control Center) Support
- ThinkColour can only be used with Windows 10 and Windows 11
- Smart Power

The Smart Power function intelligently detects overall power consumption and dynamically manages the power delivery to each device

DESIGN

Mechanical

ThinkCentre® M Series Support

ThinkCentre M Series Tiny, ThinkCentre M Series Nano For supporting Tiny devices, additional Tiny Monitor Clamp II (PN: 4XH0Z42451) are needed (sold separately). For supporting Nano devices, additional Nano Monitor Clamp II (PN: 4XH0Z42451) are needed (sold separately).

Bezel Width

- Side: 9.5mm
- Top / Bottom: 9.5mm / 28.4mm

Cable Management

Support

Case Color

Raven black

Dimensions (WxDxH)^[1]

Models	Dimensions
Lowest Position	817.3 x 245.0 x 469.3 mm (32.18 x 9.65 x 18.48 inches)
Highest Position	817.3 x 245.0 x 621.4 mm (32.18 x 9.65 x 24.46 inches)
Head Only	817.3 x 76.8 x 372.7 mm (32.18 x 3.02 x 14.67 inches)

Packaging Dimensions (WxDxH)

937 x 220 x 475 mm (36.89 x 8.66 x 18.70 inches)

Weight^[2]

Models	Weight
Monitor Head Only	7.4 kg (16.31 lbs)
Monitor With Stand	10.8 kg (23.81 lbs)

Packaging Weight

15.5 kg (34.17 lbs)

Mounting

Supports VESA mount 100mm

Stand

Supports -5° to +35° tilt, left & right 45 swivel, up to 150mm lift

In the Box

- 1x DP Cable (1.8m) (NA only)
- 1x Power cable (1.8m)
- 1x USB-C[®] to USB-A Cable (1.8m) (NA only)
- 1x USB-C to USB-C Cable (1.8m)
- Factory Calibration Report
- Monitor with Stand
- Quick Setup Guide

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

Ethernet

Support 10M / 100M / 1000M

Ports^[1]

Rear Ports^[2]

- 1x USB-C 3.2 Gen 1 (DP 1.2 Alt Mode and up to 100W PD), USB upstream
- 1x USB-C 3.2 Gen 1, USB downstream
- 1x USB-B 3.2 Gen 1, USB upstream
- 3x USB 3.2 Gen 1, USB downstream
- 2x HDMI[®] 2.0
- 1x DisplayPort[™] 1.2
- 1x DisplayPort out
- 1x Ethernet (RJ-45)
- 1x Power Connector
- 1x audio-out (3.5mm)

Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4[®] 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt[™] 3/4: 40 Gbit/s.

[2] Up to 100W power delivery to compatible devices by USB-C. Listed as maximum capacity of power delivery. Actual capacity of power delivery may vary depending upon devices connected or monitor configuration, and may decline with downstream USB ports connected or higher brightness setting.

SECURITY & PRIVACY

Security

Physical Locks

Kensington[®] Security Slot™

Warranty

Base Warranty

3-year limited warranty

CERTIFICATIONS

Green Certifications^{III}

Green Certifications

- EU Energy Label (F-class)
- ENERGY STAR[®] Certified
- EPEAT[™] Gold Registered^[2]
- TCO Certified 9.0
- RoHS compliant

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or selfdeclaration.

[2] EPEAT is registered where applicable, please see https://www.epeat.net for registration status by country.

Other Certifications

Other Certifications

- Eyesafe® Certified
- TÜV Rheinland® Flicker Free
- TÜV Rheinland Eye Comfort Certification
- TÜV Rheinland Low Blue Light
- TÜV Rheinland Low Blue Light (Hardware Solution)
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.

PSREF Product Specifications Reference











